

# SULLAIR

## CERTIFIED GLIDER PROGRAM

### 375H, 375HHAF, 425H, 425HAF

#### Portable Lubricated Rotary Screw Air Compressors

375–425 cfm at 150–200 psi ■ 10.6–12 m<sup>3</sup>/min at 10.3–14 bar

**Tier 3 Emissions Compliant**



The Sullair Certified Glider Program combines EPA compliance\* with the reliability and durability Sullair is known for.

Each 375 Series glider features a new John Deere replacement engine and remanufactured Sullair air end — Plus, all new components to finish out the package.

- New John Deere replacement engine with a two-year or 3000-hour warranty
- New components surrounding the engine and air end
- Legendary Sullair remanufactured air end

\* State and regional regulations may apply



# SULLAIR®

**Always air. Always there.®**

# SULLAIR CERTIFIED GLIDER PROGRAM TECHNICAL SPECIFICATIONS

MODEL	375H	375HHAF	425H	425HAF
<b>PERFORMANCE</b>				
Actual Delivery <i>cfm (m<sup>3</sup>/min)</i>	375 (10.6)		425 (12)	
Rated Pressure <i>psi (bar)</i>	150 (10.3)	200 (14)	150 (10.3)	
Pressure Range, <i>min/max (bar)</i>	80/150 (5.5/10.3)	80/200 (5.5/14)	80/150 (5.5/10.3)	
Sound Level <i>dBA</i>	76			
Fuel Consumption Full Load <i>gph (l/h)</i>	6.55			
Max Operating Altitude <i>ft(m)</i>	10,000 (3048)			

<b>ENGINE</b>	
Make & Model ( <i>Emissions Level</i> )	John Deere 4045HF285 (T3)
Cylinders	4
Bore & Stroke <i>in (mm)</i>	4.19 x 5.00 (106 x 127)
Rated Power <i>hp (kW)</i>	140 (104)
Rated Speed <i>rpm</i>	2200
Cooling System Capacity <i>gal (l)</i>	4 (15)
Engine Oil Capacity <i>qts (l)</i>	9 (8.5)
Fuel Tank Capacity <i>gal (l)</i>	56 (53)
Electrical System Voltage	12
Battery Rating <i>CCA</i>	1100

<b>COMPRESSOR</b>			
Service Valves No. / Size <i>in (mm)</i>	2 / 3/4 (19)	1 / 1 1/2 (38)	2 / 3/4 (19)
Compressor Oil Capacity <i>gal (l)</i>	7 (26.5)		

<b>DPQ PACKAGE — INCLUDES RUNNING GEAR</b>	
Working Weight <i>lbs (kg)</i>	4440 (2014)
Dry Weight <i>lbs (kg)</i>	4050 (1837)
Length <i>in (mm)</i>	156.2 (3967.5)
Width <i>in (mm)</i>	77.2 (1960)
Height <i>in (mm)</i>	74 (1880)
Max Towing Speed <i>mph (kph)</i>	55 (88.5)
Axle Rating <i>lbs (kg)</i>	5000 (2268)
Tire Size ( <i>load range</i> )	225/75D15